




DANA
DANA CORPORATION
FREDERICKTOWN, OHIO 4360-56
AMERICAN YARD PRODUCTS 137371

DANA CORPORATIONSERVICE PARTS REPLACEMENT LISTINGMODEL NO.: 4360-56DATE: 7-27-92DESCRIPTION: FIVE SPEED LINEAR SHIFT TRANSAXLECUSTOMER & PART NO.: AMERICAN YARD PRODUCTS - #137371

<u>KEY</u> <u>NO.</u>	<u>DANA</u> <u>PART NO.</u>	<u>A.Y.P.</u> <u>PART NO.</u>	<u>NO.</u> <u>REQ'D.</u>	<u>DESCRIPTION</u>
1	5305		1	Housing, Upper
2	1919	2274J	14	Screw, Tapping, 1/4-20 X .734 Lg.
3	5112		2	Ball, Detent
4	3626	105904X	2	Spring, Detent
5	3623	105905X	2	Screw, Set
6	4604		1	Kit, Shifter Ass'y.
7	5024		1	Boot, Shifter
8	3907	120951X	1	Puck, Friction
9	5131		2	Screw, Tapping, w/Sealer
10	4816		1	Ass'y., Kit, Ring, Retaining
11	4689		3*	Ass'y., Kit, Shim, .625 Shaft
12	3866	120407X	1	Gear, Spur, 20T.
13	3876	120415X	2	Washer, Plain, .632 X 1.38 X .046
14	1374	2257J	1	Key, Woodruff, #9
15	4171	106846X	1	Ass'y., Kit, Input Shaft
16	3725	106095X	1	Pinion, Bevel, 14T.
17	3624	105909X	1	Ring, Retaining
18	3625	105910X	1	Chain, 24 Pitches
19	1542	105911X	3	Bearing, Flange
20	5280		1	Gear, Spur, 14T.
21	5303		1	Collar, Clutch
22	4760		1	Ass'y., Kit, Clutch Keys
23	5278		1	Bearing, Flange
24	5299		1	Shaft, Intermediate
25	1375	2244J	1	Key, Woodruff, #61
26	3627	105916X	1	Ring, Retaining
27	3830	120470X	1	Sprocket, 18T.
28	3841	110070X	1	Spacer
29	3786	108977X	1	Gear, Spur, 37T.
30	3867	124644X	1	Gear, Spur, 30T.
31	3783	108980X	1	Gear, Spur, 25T.
32	3869	120406X	1	Gear, Spur, 22T.
33	5202		1	Gear, Spur, 19T.
34	5027		1	Spacer, 1.133 X 1.50 X .375
35	3628	105925X	1	Washer, Plain, .640 X 1.37 X .061
36	1423	2232J	2	Washer, Plain, .632 X 1.00 X .026
37	3422	108978X	1	Spacer, .630 X 1.00 X .169
38	4286	110079X	1	Ass'y., Gear, Comb., 12T. & 35T.
39	3967	124639X	1	Shaft, Idler

Model #4360-56

Page 2

<u>KEY</u> <u>NO.</u>	<u>DANA</u> <u>PART NO.</u>	<u>A.Y.P.</u> <u>PART NO.</u>	<u>NO.</u> <u>REQ'D.</u>	<u>DESCRIPTION</u>
40	3901	120472X	1	Spacer, .633 X .87 X .755
41	3645	105928X	1	Sprocket, 9T.
42	3589	106605X	1	Gear, Bevel, 42T.
43	4691		2*	Ass'y., Kit, Shim, .750 Shaft
44	3882	120473X	1	Shaft, Drive
45	3724	106596X	1	Screw, Tapping, 5/16-18 X 1.44 Lg.
46	3646	105933X	1	Gear, Spur, 12T.
47	3719	106589X	1	Gear, Spur, 25T.
48	3868	120408X	1	Gear, Spur, 28T.
49	3683	105937X	1	Gear, Spur, 31T.
50	3714	105936X	1	Spacer, .781 X 1.00 X .375
51	1145	2226J	1	Washer, Plain, .632 X 1.00 X .060
52	5130		2	Washer, Neoprene
53	3184	2264J	2	Washer, Plain, .758 X 1.25 X .031
54	3880	120474X	1	Axle, L.H.
55	3871	120409X	2	Gear, Miter, 15T.
56	3656	105941X	2	Ring, Retaining
57	3839	110071X	1	Gear, Spur, 32T.
58	3919	120952X	1	Shaft, Cross
59	3726	106592X	2	Gear, Miter, 15T.
60	3881	120475X	1	Axle, R.H.
61	5304		1	Housing, Lower
62	3920	120961X	1	Puck, Friction
63	3276	7294J	1	Disc, Brake
64	3758	108989X	1	Spacer
65	3916	120953X	1	Jaw, Brake
66	3843	120954X	2	Pin, Dowel
67	5120		1	Screw, Tapping, 5/16-18 X 2.25
68	5285		1	Lever, Actuating
69	3760	108996X	1	Washer, Plain, .321 X 1.00 X .055
70	3917	120956X	1	Bracket, Anti-Rotation
71	3847	73810500	1	Nut, Lock, 5/16-24
72	5279		1	Square-Ring
73	4300	120416X	1	Grease

* Use in various combinations to maintain proper clearances.

** Order Key No. 15.