



## NOTES

1. CENTER WINDOWS IN WALLS, UNO. SEE ELEVATIONS FOR WINDOW DIMENSIONS AND OPERABILITY.
2. ALIGN NEW EXTERIOR WALLS WITH EXISTING WALLS TO REMAIN BELOW.

## LEGEND

45 ANGLE DOORS = EXISTING TO REMAIN

POCHE PARTITIONS = EXISTING TO REMAIN

P-1 1-1/2+ HR RATED (SIM UL U935), 1/2" GYP BD ON 2X4 STUDS, SET SIDEWAYS, WITH SPRAY INSUL?, AT EXISTING BRICK WALL, SEE SECTION 2/A23

P-2 1-HR RATED (UL U356), 5/8" GYP BD ON 2X4 STUDS 16"OC, SHIM AS NEEDED TO ALIGN W/ ADJACENT FURRED PARTITION, BATT INSULATION R-13 MIN, 1/2" PLYWD SHEATHING, BLDG WRAP, HARDIPLANK LAP SIDING, SEE SECTION 1/A23

P-3 1/2" GYP BD ON 2X6 STUDS 16"OC, BATT INSULATOIN R-13 MIN, 1/2" PLYWD SHEATHING, BLDG WRAP, HARDIPLANK LAP SIDING, SEE SECTION 1/A22

P-4 1/2" GYP BD BOTH SIDES, 2X4 STUDS 16"OC

P-5 1/2" GYP BD, 2X2 FURRING ON EXISTING BRICK WALL

P-6 1/2" GYP BD, 2X4 FURRING (FOR PLUMBING) ON EXISTING BRICK

P-7 CERAMIC TILE @ BATH, ON CEMENTITIOUS BACKER BOARD, ON 2X4 STUDS

P-8 CERAMIC TILE @ BATH, ON CEMENTITIOUS BACKER BOARD, ON EXISTING WALL TO REMAIN

### NOTES:

1. AT EXTERIOR WALLS ON EXISTING BRICK, SEAL INSIDE OF BRICK WALL AND USE TREATED LUMBER TO PREVENT MOISTURE AFFECTS.
2. WHERE UL NUMBERS ARE LISTED FOR FIRE-RATED PARTITIONS, REFER TO UL FOR COMPLETE STANDARDS, DESCRIPTIONS, AND DETAILS
3. APPLY FIRE-RATED SEALANT AND STOPPING AT ALL JOINTS AND PENETRATIONS